

Isolating Switches DX³-IS

from 16A to 125A



AC 22 A according to IEC 60947-3;

Double breaking contacts;

Can be equipped with 1 DX³ signalling auxiliary;

Modules	In, A	Category Number	Quantity/Pack
1-pole 250VAC			
16		4 064 00	12/120
20		4 064 01	12/120
32		4 064 03	12/120
40		4 064 11	12/120
63		4 064 12	12/120
100		4 064 23	12/120
2-pole 400VAC			
16		4 064 31	6/60
20		4 064 32	6/60
32		4 064 33	6/60
40		4 064 40	6/60
63		4 064 41	6/60
100		4 064 49	6/60
125		4 064 50	6/60
3-pole 400VAC			
20		4 064 57	4/40
32		4 064 59	4/40
40		4 064 60	4/40
63		4 064 61	4/40
100		4 064 69	4/40
125		4 064 70	4/40
4-pole 400VAC			
20		4 064 77	3/30
32		4 064 79	3/30
40		4 064 80	3/30
63		4 064 81	3/30
100		4 064 89	3/30
125		4 064 90	3/30

RCBOs DX³ 6000

residual current breakers with overload protection, 6-63A



Conform to IEC 61009-1;

Breaking Capacity, 6000-IEC 61009-1;

Enhanced immunity to unwanted tripping in disturbed environment

Modules	In, A	Sensitivity, mA	Category Number	Quantity/Pack
Single pole + N, 230VAC, AC Type				
16	10		4 109 93	1/60
6	30		4 109 99	1/60
10	30		4 110 00	1/60
16	30		4 110 02	1/60
20	30		4 110 03	1/60
25	30		4 110 04	1/60
32	30		4 110 05	1/60
40	30		4 110 06	1/60
6	300		4 110 21	1/60
10	300		4 110 22	1/60
16	300		4 110 24	1/60
20	300		4 110 25	1/60
25	300		4 110 26	1/60
32	300		4 110 27	1/60
40	300		4 110 28	1/60
Single pole + N, 230VAC, A Type				
16	10		4 110 41	1/60
6	30		4 110 47	1/60
10	30		4 110 48	1/60
16	30		4 110 50	1/60
20	30		4 110 51	1/60
25	30		4 110 52	1/60
32	30		4 110 53	1/60
40	30		4 110 54	1/60